

# Declaration of Performance

N° DoP: 08-005 2020-06-20

Unique identification code of the product-type

**Corrugated bitumen sheet - Category S**

Intended use/es

- Discontinuously laid pitched roof coverings for buildings  
- Discontinuously laid external wall finishes for buildings

Manufacturer

Onduline Materiales de Construcción S.A.  
Polígono Industrial El Campillo, Fase II, Parcela 12 | 48500 GALLARTA – ESPAÑA  
Tel. +34 946 369 444 | email: tecnico-onduline@onduline.es

System/s of AVCP

System 3 (reaction to fire) | System 4 (other performances)

Harmonised standard

EN 534:2006+A1:2010

Notified body/ies

1239 - CIDEMCO - Spain

Declared performances

Essential characteristics	Performance	Harmonised standard
Bending under downward load	> 700 N/m <sup>2</sup>	EN 534:2006+A1:2010
Impact strength	250 mm	
Tearing strength	> 150 N	
Tearing strength after freeze/thaw ageing	> 150 N	
Water permeability	Pass	
Water permeability after freeze/thaw ageing	Pass	
Thermal coefficient	< 100.10-6 1/K	
Reaction to fire	E	
External fire performance	Froof	
Dangerous substances	NPD*	

\*NPD: No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number: v02

Signed for and on behalf of the manufacturer by

BUGALLO Alfonso  
Onduline Iberia General Manager  
Gallarta, 24.01.2024