

# Declaration of Performance

N° DoP: 2021-001 SA34



Unique identification code of the product-type:	<b>ONDUTISS® STRONG STD</b>
Intended use/es:	Flexible sheets for underlays which are to be used under roof covering of discontinuous roofs
Manufacturer:	<b>Onduline</b> 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	<b>System 3</b>
Harmonised standard :	<b>EN 13859-1:2010</b>
Notified body/ies:	<b>0071 - Laboratoire National de métrologie et d'Essais (LNE)</b>

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	E	-	-	<b>EN 13859-1:2010</b>
Watertightness (class)	W1	-	-	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	450 / 250	±15% / ±15%		
Elongation at maximum load (longitudinal/transverse direction) (%)	25-45 / 30-50	-	-	
Resistance to tearing (longitudinal/transverse direction) (N)	150 / 170	±15% / ±15%		
Flexibility at low temperature (pliability) (°C)	-40	-	-	
Durability of resistance to water penetration (class)	W1	-	-	
Durability of tensile strength (longitudinal/transverse direction) (N/50mm)	440 / 245	±15% / ±15%		
Durability of elongation (longitudinal/transverse direction) (%)	NPD	-	-	
Dangerous substances	NPD			

**NPD\* : No Performance Determined**

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay TAWILE', is written over a horizontal line.

Nay TAWILE  
Suresnes, 14/06/2024