

# Declaration of Performance

N° DoP: 2021-006 SA20



Unique identification code of the product-type:

**ONDUTISS® BUILD FOIL 0,15mm**

Intended use/es:

Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings

Manufacturer:

**Onduline**  
5-7 rue Frédéric Clavel  
92150 Suresnes - France

System/s of AVCP:

**System 3**

Harmonised standard :

**EN 13984:2013**

Notified body/ies:

**1434 - POLSKIE CENTRUM BADAN I CERTYFIKACJI S.A.**

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	F	-	-	EN 13984:2013
Watertightness (2kPa,24h)	Pass	-	-	
Resistance to impact (mm)	NPD	-	-	
Diffusion resistance (water vapour) - (m <sup>2</sup> .s.Pa/kg)	4,8.10 <sup>11</sup>	±75%		
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥15 / ≥15	-	-	
Elongation at maximum load (longitudinal/transverse direction) (%)	≥150 / ≥150	-	-	
Resistance to tearing (longitudinal/transverse direction) (N)	≥40 / ≥40	-	-	
Joint strength (N/50mm)	NPD	-	-	
Durability Against Aging	Pass	-	-	
Durability against chemical resistance (alkali)	NPD	-	-	
Dangerous substances	NPD	-	-	

**NPD\* : No Performance Determined**

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay Tawile', is written over a horizontal line.

Nay TAWILE  
Suresnes, 17/06/2024