

Declaration of Performance

N° DoP: 2021-007 SA20



Unique identification code of the product-type:	ONDUTISS® BUILD FOIL 0,2mm
Intended use/es:	Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings
Manufacturer:	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	System 3
Harmonised standard :	EN 13984:2013
Notified body/ies:	1434 - POLSKIE CENTRUM BADAN I CERTYFIKACJI S.A.

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	F	-	-	EN 13984:2013
Watertightness (2kPa,24h)	Pass	-	-	
Resistance to impact (mm)	NPD	-	-	
Diffusion resistance (water vapour) - (m ² .s.Pa/kg)	4,8.10 ¹¹	±75%		
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥60 / ≥50	-	-	
Elongation at maximum load (longitudinal/transverse direction) (%)	≥150 / ≥150	-	-	
Resistance to tearing (longitudinal/transverse direction) (N)	≥40 / ≥40	-	-	
Joint strength (N/50mm)	NPD	-	-	
Durability Against Aging	Pass	-	-	
Durability against chemical resistance (alkali)	NPD	-	-	
Dangerous substances	NPD	-	-	

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay Tawile', is written over a horizontal line.

Nay TAWILE
Suresnes, 17/06/2024