

Declaration of Performance

N° DoP: 2021-008 SA20



| | |
|---|--|
| Unique identification code of the product-type: | ONDUTISS® BUILD FOIL 0,3mm |
| Intended use/es: | Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings |
| Manufacturer: | Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France |
| System/s of AVCP: | System 3 |
| Harmonised standard : | EN 13984:2013 |
| Notified body/ies: | 1434 - POLSKIE CENTRUM BADAN I CERTYFIKACJI S.A. |

Declared performances:

| Essential characteristics | Performance | Tolerance | | Harmonised standard |
|--|----------------------|-----------|---------|---------------------|
| | | minimum | maximum | |
| Reaction to fire (class) | F | - | - | EN 13984:2013 |
| Watertightness (2kPa,24h) | Pass | - | - | |
| Resistance to impact (mm) | NPD | - | - | |
| Diffusion resistance (water vapour) - (m ² .s.Pa/kg) | 4,8.10 ¹¹ | ±75% | | |
| Tensile strength (longitudinal/transverse direction) (N/50 mm) | ≥60 / ≥50 | - | - | |
| Elongation at maximum load (longitudinal/transverse direction) (%) | ≥150 / ≥150 | - | - | |
| Resistance to tearing (longitudinal/transverse direction) (N) | ≥40 / ≥40 | - | - | |
| Joint strength (N/50mm) | NPD | - | - | |
| Durability Against Aging | Pass | - | - | |
| Durability against chemical resistance (alkali) | NPD | - | - | |
| Dangerous substances | NPD | - | - | |

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay TAWILE', is written over a horizontal line.

Nay TAWILE
Suresnes, 17/06/2024