Declaration of Performance

N° DoP: 2024-001 SA52



Unique identification code of the product-type:	ONDUBAND® EASY
Intended use/es:	Vapor barrier membrane sealing layer
Manufacturer:	Onduline 24, quai Gallieni 92150 Suresnes - France
System/s of AVCP:	System 3
Harmonised standard :	DIN EN 13970
Notified body/ies:	1742 - Baustofflabor Nord GmbH

Declared performances:

Essential characteristics	Performance	Tole minimum	erance maximum	Harmonised standard	
Reaction to fire (class)	E	-	-		
Watertightness - method B	Pass	-	-		
Thickness (mm)	≥1,0 ± 0,3				
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥180 / ≥180	±10%		DIN EN 13970	
Elongation at maximum load (longitudinal/transverse direction) (%)	≥20 / ≥20	-	-	- DIN EN 13970	
Flexibility at low temperature (pliability) (°C)	NPD	-	-		
Water vapor permeability (sd value) (m)	>1500	-	-		
Dangerous substances ^{1), 2)}	Requiremet met, see 5.14 EN 13970				

NPD* : No Performance Declared

1) Product contains no asbestos and no tar

2) Since there is no European test method, no statement can be made on this.

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsability of the manufacturer identified above.

Version number : v01

Herenner -

Signed for and on behalf of the manufacturer by:

Nay TAWILE Suresnes, le 04/06/2024

www.onduline.com