

Declaration of Performance

N° DoP: 2024-002 SA52



Unique identification code of the product-type:	ONDUBAND® PRO
Intended use/es:	Vapor barrier membrane sealing layer
Manufacturer:	Onduline 24, quai Gallieni 92150 Suresnes - France
System/s of AVCP:	System 3
Harmonised standard :	DIN EN 13970
Notified body/ies:	1742 - Baustofflabor Nord GmbH

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	E	-	-	DIN EN 13970
Watertightness - method B	Pass	-	-	
Thickness (mm)	$\geq 1,5 \pm 0,3$			
Tensile strength (longitudinal/transverse direction) (N/50 mm)	$\geq 200 / \geq 200$		$\pm 10\%$	
Elongation at maximum load (longitudinal/transverse direction) (%)	$\geq 20 / \geq 20$	-	-	
Flexibility at low temperature (pliability) (°C)	NPD	-	-	
Water vapor permeability (sd value) (m)	>1500	-	-	
Dangerous substances ^{1), 2)}	Requirement met, see 5.14 EN 13970			

NPD* : No Performance Declared

1) Product contains no asbestos and no tar

2) Since there is no European test method, no statement can be made on this.

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v01

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay Tawile', with a horizontal line extending to the right.

Nay TAWILE

Suresnes, le 04/06/2024