

Declaration of Performance

N° DoP: 2014-040 SA43



Unique identification code of the product-type:	FONDALINE® PLASTER 600
Intended use/es:	Flexible sheets for waterproofing intended to be used as damp proofing for buildings, including basement tanking - Type V
Manufacturer:	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	System 2+
Harmonised standard :	EN 13967:2012
Notified body/ies:	1213 - SKZ - Testing GmbH

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		min	max	
Reaction to fire (class)	F	-	-	EN 13967:2012
Watertightness (60 kPa,24h)	Pass	-	-	
Resistance to tearing (longitudinal/transverse direction) (N)	NPD	-	-	
Joint strength (N/50mm)	NPD	-	-	
Resistance to impact (mm) - method A	700	-	-	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	300 / 300	-	-	
Elongation at maximum load (longitudinal/transverse direction) (%)	20 / 15	-	-	
Resistance to static loading (kg)	NPD	-	-	
Durability against aging	NPD	-	-	
Durability against chemical resistance (alkali)	NPD	-	-	
Dangerous substances	Less than required by national regulations in EU Member States	-	-	

NPD : No Performance Determined*

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

A handwritten signature in black ink, appearing to read 'Nay Tawile', written over a horizontal line.

Signed for and on behalf of the manufacturer by:

Nay TAWILE
Suresnes, 21/06/2024