Declaration of Performance

N° DoP: 2017 J 003



Unique identification code of the product-type:

ONDUTISS® VAPCONTROL 4S 170

Intended use/es:

Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings

Manufacturer:

Onduline

5-7 rue Frédéric Clavel 92150 Suresnes - France

System/s of AVCP:

System 3

Harmonised standard:

EN 13984:2013

Notified body/ies:

1023 - INSTITUT PRO TESTOVÁNI A CERTIFIKACI,

a. s. (INSTITUTE FOR TESTING AND CERTIFICATION) merged with ex-NB 1390

Declared performances:

Essential characteristics	Performance	Tole minimum	rance maximum	Harmonised standard
Reaction to fire (class)	E	-	-	EN 13984:2013
Watertightness (2kPa,24h)	Pass	-	-	
Resistance to impact (mm)	NPD	-	-	
Diffusion resistance (water vapour) - (m².s.Pa/kg)	NPD	-	-	
Water vapour resistance factor Sd (m)	3	-2	+3	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	>350 / >290	-	-	
Elongation at maximum load (longitudinal/transverse direction) (%)	NPD	-	-	
Resistance to tearing (longitudinal/transverse direction) (N)	>240 / > 240	-	-	
Joint strength (N/50mm)	NPD	-	-	
Water vapor transmission properties after artificial aging	Pass	-	-	
Durability against chemical resistance (alkali)	NPD	-	-	
Dangerous substances	NPD	-	-	

NPD* : No Performance Declared

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsability of the manufacturer identified above.

Version number: v03

Signed for and on behalf of the manufacturer by:

Nay TAWILE

Suresnes, 25/06/2024