N° DoP: 2024-001 SA20



Unique identification code of the product-type:	ONDUTISS® VAPCONTROL 150 SD5
Intended use/es:	Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings
Manufacturer:	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	System 3
Harmonised standard :	EN 13984:2013
Notified body/ies:	1301 - Technicky a skusobny ustav stavebny, n. o.

Declared performances:

Essential characteristics	Performance	Tolerance minimum maximum	Harmonised standard
Reaction to fire (class)	E		- ±25% EN 13984:2013
Watertightness (2kPa,24h)	Pass		
Diffusion resistance (water vapour) - (m ² .s.Pa/kg)	11,97.10 ⁹	±25%	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥260 / ≥150		
Elongation at maximum load (longitudinal/transverse direction) (%)	≥45 / ≥50		
Resistance to tearing (longitudinal/transverse direction) (N)	≥130 / ≥160		
Joint strength (N/50mm)	NPD		
Durability Against Aging	Pass		
Durability against chemical resistance (alkali)	Pass		
Dangerous substances	NPD		

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsability of the manufacturer identified above.

Version number : v02

Sig

Signed for and on behalf of the manufacturer by:

Nay TAWILE Suresnes, 19/06/2024

www.onduline.com