

Declaration of Performance

N° DoP: 2024-003 SA20



Unique identification code of the product-type:

**ONDUTISS® VAPCONTROL 220, ONDUTISS® VAPCONTROL 220 T,
ONDUTISS® VAPCONTROL 220 TT**

Intended use/es:

Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings

Manufacturer:

Onduline
24, quai Gallieni
92150 Suresnes - France

System/s of AVCP:

System 3

Harmonised standard :

EN 13984:2013

Notified body/ies:

1301 - Technicky a skusobny ustav stavebny, n. o.

Declared performances:


Essential characteristics	Performance	Harmonised standard
Reaction to fire	E	EN 13984:2013
Watertightness (at 2kPa)	Pass	
Resistance to impact (mm)	≥300	
Resistance to tearing (longitudinal/transverse direction) (N)	≥200 / ≥285	
Joint strength (N)	NPD	
Water vapour transmission properties (m)	5 (±2)	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	≥320 / ≥210	
Elongation at maximum load (longitudinal/transverse direction) (%)	≥45 / ≥50	
Durability - water vapour resistance (after artificial ageing)	Pass	
Durability - Chemical resistance	Pass	
Dangerous substances	NPD	

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v01

Signed for and on behalf of the manufacturer by:


Nay TAWILE
- Suresnes, le 13/02/2024